

## Comet P Series Diaphragm Pump Selection Guide

1-320-243-8030 FAX

SPRAYER ACCESSORIES






COMET PUMPS



### P SERIES DIAPHRAGM PUMPS

Plastic (P36) or plastic coated aluminum (P48) heads with plastic manifolds for premium corrosion resistance. Great for mild acids and mold removal agents, as well as agriculture, lawn care and pest control.

- Part numbers may vary depending on diaphragm materials. Call for specific pump part numbers.
- Some pumps shown with OPTIONAL control valve or PTO shield.
- We recommend a shaft cover or protector with all male shaft applications.
- Performance charts, drive options & dimensional drawings are available at [www.COMETPUMPUSA.com](http://www.COMETPUMPUSA.com)

Model	Max GPM	Max PSI	Description	In	Out	Bypass	Wt. Lbs
 P36	9.6	150	Three diaphragm pump with 30mm solid keyed shaft and mounting rails.	1"	*	*	17.6
 P36-GR	9.6	150	Three diaphragm pump with gear reduction for 3/4" shaft. Includes pressure regulator with manual dump lever and mounting rails.	1"	3/8"	3/4"	24
 P48	13.5	435	Twin diaphragm pump with universal drive face.	1"	*	*	28
 P48-TS	13.5	435	Twin diaphragm pump with universal drive face to 1" solid keyed through shaft.	1"	*	*	28
 P48-GR	13.5	435	Twin diaphragm pump with gear reduction for gas engines with 3/4" shaft. Includes pressure regulator with manual dump lever.	1"	3/8"	3/4"	34