
Comet APS Series Diaphragm Pump Selection Guide



1-320-243-8030 FAX

SPRAYER ACCESSORIES

COMET PUMPS

0

APS SERIES DIAPHRAGM PUMPS

High pressure internal manifold pumps with anodized aluminum heads for less leak points. Great for lawn care, pest control, hydrostatic testing and agricultural spraying.

- Part numbers may vary depending on diaphragm materials. Call for specific pump part numbers.
 Some pumps shown with OPTIONAL control valve or PTO shield.

- We recommend a shaft cover or protector with all male shaft applications.
 Performance charts, drive options & dimensional drawings are available at www.COMETPUMPUSA.com

Model	Max GPM	Max PSI	Description	In	Out	Bypass	Wt. Lbs
APS51-GR5	14.5	350	Three diaphragm pump with gear reduction for gas engines with 3/4" shaft. Includes pressure regulator with manual dump lever.	1 1/4"	1/2"	1"	43
APS51-GR8	14.5	580	Three diaphragm pump with gear reduction for gas engines with 1" shaft. Includes pressure regulator with manual dump lever.	1 1/4"	1/2"	1"	44
APS71	18	725	Three diaphragm pump with universal drive face.	1 3/8"	•	•	40
APS71-MF	18	725	Three diaphragm pump with universal drive face on front and 1 3/8" male 6 spline PTO shaft on back.	1 <mark>3/8</mark> "	•	•	40
APS71-MM	18	725	Three diaphragm pump with 1 3/8" male 6 spline PTO shaft on both sides.	1 3/8"	•		40
APS71-GR5	1 18	350	Three diaphragm pump with gear reduction for gas engines with 3/4" shaft. Includes pressure regulator with manual dump lever.	1 1/4"	1/2"	1"	48

SPRAYER ACCESSORIES

1-800-864-1649 TOLL FREE

COMET PUMPS

APS SERIES DIAPHRAGM PUMPS



High pressure internal manifold pumps with anodized aluminum heads for less leak points. Great for lawn care, pest control, hydrostatic testing and agricultural spraying.

- Part numbers may vary depending on diaphragm materials. Call for specific pump part numbers.
 Some pumps shown with optional control valve or PTO shield.
- · We recommend a shaft cover or protector with all male shaft applications.
- Performance charts, drive options & dimensional drawings are available at www.COMETPUMPUSA.com

Model	Max GPM	Max PSI	Description	In	Out	Bypass	Wt. Lbs
APS71-GR8	18	725	Three diaphragm pump with gear reduction for gas engines with 1" shaft. Includes pressure regulator with manual dump lever.	1 1/4"	1/2"	1"	49
APS96	24	725	Four diaphragm pump with universal drive face. Includes pressure regulator with manual dump lever and mounting rails.	1 1/2"	•	1"	50
APS96-MF	24	725	Four diaphragm pump with universal drive face on front and 1 3/8" male 6 spline PTO on back.	1 1/2"	•	•	50
APS96-MM	24	725	Four diaphragm pump with 1 3/8" male 6 spline PTO shaft on both sides.	1 1/2"	•	•	50
APS101	26	725	Three diaphragm pump with 1 3/8" male 6 spline PTO shaft on both sides.	1 1/2"	•	•	84
APS121	30	725	Three diaphragm pump with 1 3/8" male 6 spline PTO shaft on both sides.	1 1/2"	•	•	84
APS145	37	725	Four diaphragm pump with 1 3/8" male 6 spline PTO shaft on both sides. Includes pressure regulator with manual dump lever.	1 3/4"	1/2"	1"	10