

To install shut off valves:

Step 1: Turn off the water supply to the system.

Step 2: Cut both the clear and black tubing 2" from the blue and green connector nuts.

Step 3: Slide washers over the tubing connected to the cap.

Step 4: Insert the tubing until it stops, into each end of the valves.

To refill unit:

Step 1: Turn off both the water in and fertilizer out shut off valves.

Step 2: Disconnect tubing from both valves by pressing the disconnect washer into the ring at the end of the valve, on the valve tubing connection closest to the tank cap and pulling the tubing from the valve.

Step 3: Remove tank cap by unscrewing it in a counter clockwise direction.

Step 4: Pour all but 2" of water from the tank.

Step 5: For maximum performance of your system, **ADD the recommended amount of fertilizer listed below for your tank size.** Pour the recommended amount of dry fertilizer directly into the tank (funnel recommended).

No need to premix dry fertilizer

<u>Model</u> <u>Amount</u>	<u>Tank Size</u>	<u>Rec.</u>
EZ001 dry or gal. liquid	1.5 gallon	10 lbs 1.5
EZ003 dry or gal. liquid	3 gallon	15 lbs 3
EZ005 dry or gal. liquid	5 gallon	25 lbs 5

Use only manufacturer-approved water-soluble or organic fertilizer. It is not recommended to use any other chemicals in unit.

Step 6 - Fill until full using the water to liquefy and mix the fertilizer. Fill until water begins to run out of the tank neck to ensure all air is eliminated.

Step 7 - Screw cap on tank by turning in a clockwise direction. (Do not over tighten cap)

Step 8 - Replace disconnect washer on

the tubing connected to the tap.

Step 9 - Connect tubing to shut off valve by pressing it firmly into the open end of the valve. Turn both valves to the ON position.