

VFX Series Aerating Fountains

Aerating Fountains Providing the Highest Oxygen Transfer Rates & Pleasing Displays



A PERFECT COMBINATION OF AERATION & AESTHETICS

Kasco's VFX Aerating fountains set the standard by which all aerating fountains are measured. Delivering both superior aerating performance as well as an impressive and beautiful visual display, these fountains are sure to deliver the water quality results you are looking for. Kasco's VFX series are versatile, dependable units and can be used in any application where aeration and beautification are desired. Choose from our LED composite or stainless steel light kits or RGB color changing lights to extend the enjoyment of your fountain into the evening hours.

- Available in 1/2, 3/4, 1, 2 and 5HP options
- Can operate in as little as 15 in. of water
- Self-contained floating units
- V-shaped circular display patterns
- Outstanding oxygen transfer rates
- Extremely efficient with low operating costs
- Durable and corrosion resistant
- Unique clog-resistant design
- 2 year warranty on 1/2, 3/4 and 1HP units
- 3 year warranty on 2 and 5HP units



EASY TO USE & INSTALL

Kasco's VFX Aerating Fountains are easy to install, move and operate. These units ship with the control panel, GFI, photo-eye for optional light kit, power cord and mooring lines. Easily installed in less than an hour!

COST-EFFECTIVE & ENERGY EFFICIENT

Kasco's VFX Aerating Fountains are the least expensive to purchase, maintain, repair and operate. The low power consumption makes continuous use of Kasco's VFX fountains affordable on any budget.

INDUSTRIAL STRENGTH

Designed with heavy-duty stainless steel components for continuous operation, extended motor life and corrosion prevention even in salt water. They are the least likely fountains to clog in the industry thanks to our exclusive deflector technology, prop guard and standard bottom intake screen.

VERSATILE

Kasco's VFX fountains are available from 1/2-5HP in a multitude of power options including 120V, 240V, 460V, single phase and 3 phase. Power cord lengths are available as 50, 100, 150, 200, 250, 300, 400 and 500 ft. Check the part number table below for specific power and cord length options.

COMPLIANT & WARRANTED

Approved to UL and CSA standards by ETL as complete packages and carries a 2 year warranty on the 1/2-1HP and a 3 year warranty on the 2 & 5HP.



VFX Aerating Fountain Model Numbers & Specifications

60 HZ MODELS	PATTERN SIZE	HP	VOLTAGE	AMPS	RECOMMENDED POND SIZE (SQ. A)	MIN. DEPTH OF WATER
2400VFX	5 ft. H x 15 ft. W	1/2	120	5.6	Up to 1/3 acre	15 in.
3400VFX	5.5 ft. H x 21 ft. W	3/4	120	7.3	Up to 1/2 acre	17.5 in.
3400HVFX	5.5 ft. H x 21 ft. W	3/4	240	3.7	Up to 1/2 acre	17.5 in.
4400VFX	8 ft. H x 26 ft. W	1	120	11.3	Up to 3/4 acre	19 in.
4400HVFX	8 ft. H x 26 ft. W	1	240	5.7	Up to 3/4 acre	19 in.
8400VFX	8 ft. H x 32 ft. W	2	240	11	Up to 1 1/4 acre	24 in.
2.3VFX	8 ft. H x 32 ft. W	2	230, 3 Phase	7.5	Up to 1 1/4 acre	24 in.
5.1VFX	9 ft. H x 34 ft. W	5	240	20	Up to 2 acres	26 in.
5.3VFX	9 ft. H x 34 ft. W	5	230, 3 Phase	16	Up to 2 acres	26 in.

