

Model # Specifications
F2400/AF 1/2HP, 120V High Oxygen Transfer Aerator with black float ring. Produces a crown of foam at the surface and 1.5 pounds of oxygen/hour. Standard Features: 50' power cord, and two 50' black ropes for anchoring. Minimum depth 15", running Amps 5.0
F3400/AF 3/4HP, 120V High Oxygen Transfer Aerator with black float ring. Produces a crown of foam at the surface and 2.2 pounds of oxygen/hour. Standard Features: 50' power cord, and two 50' black ropes for anchoring. Minimum depth 18", running Amps 6.7
F3400/HAF 3/4HP, 240V High Oxygen Transfer Aerator with black float ring. Produces a crown of foam at the surface and 2.2 pounds of oxygen/hour. Standard Features: 50' power cord and three 50' black ropes for anchoring. Minimum depth 18", running Amps 3.4
4400/AF 1HP, 240V High Oxygen Transfer Aerator with black 3-section float. Produces a crown of foam at the surface. Standard Features: 50' power cord, and three 50' black ropes for anchoring. Minimum depth 19", running Amps 11.3
4400H/AF 1HP, 240V High Oxygen Transfer Aerator with black 3-section float. Produces a crown of foam at the surface. Standard Features: 50' power cord, and three 50' black ropes for anchoring. Minimum depth 19", running Amps 5.7
8400/AF 2HP, 240V High Oxygen Transfer Aerator with black 3-section float. Produces a crown of foam at the surface. Standard features: 50' power cord, and three 50' black ropes for anchoring. Minimum depth 20", running Amps 10