

Medium Pressure, 3 Diaphragm

Model 9910-D403 and D403GRGI

*All HP requirements listed in the table below are electrical.
For approximate gasoline equivalent, multiply by 1.3.*

Pressure in PSI and BAR	GPM	HP	GPM	HP	GPM	HP	GPM	HP
	LPM	HP	LPM	HP	LPM	HP	LPM	HP
	@350 RPM		@450 RPM		@500 RPM		@550 RPM	
0 PSI	6.3	0.7	8.1	1.0	9.0	1.1	10.6	1.2
0 BAR	23.8	0.7	30.6	1.0	34	1.1	40	1.2
290 PSI	6.1	1.3	7.7	1.7	8.7	1.9	9.8	2.1
20 BAR	23	1.3	29	1.7	32.9	1.9	37.1	2.1
435 PSI	6.0	1.9	7.7	2.4	8.6	2.7	9.7	2.9
30 BAR	22.7	1.9	29	2.4	32.5	2.7	36.7	2.9
580 PSI	5.9	2.3	7.7	2.8	8.6	3.4	9.5	3.8
40 BAR	22.3	2.3	29	2.8	32.5	3.4	35.9	3.8



HYPRO

**Pentair Water
SPRAY GROUP**

375 Fifth Avenue NW • New Brighton, MN 55112-3288
Phone: (651) 766-6300 • 800-424-9776 • Fax: 800-323-6496
www.hypropumps.com