

Medium Pressure, 2 Diaphragm

Model 9910-D252, D252GRGI and D252GRGI58

*All HP requirements listed in the table below are electrical.
For approximate gasoline equivalent, multiply by 1.3.*

Pressure in PSI and BAR	GPM	HP	GPM	HP	GPM	HP
	LPM	HP	LPM	HP	LPM	HP
	@ 450 RPM		@ 500 RPM		@ 650 RPM	
50 PSI	4.2	.33	5.1	.43	6	.53
3.5 BAR	15.8	.33	19.2	.43	22.7	.53
100 PSI	4.1	.37	5	.47	5.9	.57
7 BAR	15.4	.37	18.8	.47	22.3	.57
150 PSI	4	.4	4.9	.5	5.8	.6
10.5 BAR	15.2	.4	18.6	.5	22	.6
200 PSI	3.8	.5	4.7	.6	5.5	.8
14 BAR	14.5	.5	17.8	.6	21	.8
275 PSI	3.6	.6	4.5	.8	5.3	1
19.3 BAR	13.8	.6	17	.8	20	1
363 PSI	3.4	.9	3.8	1.0	4.6	1.2
25 BAR	13.0	.9	14.5	1.0	17.5	1.2



HYPRO[®]

**Pentair Water
SPRAY GROUP**

375 Fifth Avenue NW • New Brighton, MN 55112-3288
Phone: (651) 766-6300 • 800-424-9776 • Fax: 800-323-6496
www.hypropumps.com