



Dimensions		
Standard	mm	
A.	5.13	130
B.	2.56	65
C.	4.25	108
D.	6.63	168
E.	3.50	89
F.	4.31	109.5
G.	1.81	46
H. Hollow Shaft		
	0.88	22
H. Solid Shaft		
	1.25	32

Order Information

Model Number	Max GPM	Max PSI	Max RPM	Shaft Output	Plunger Material
5321C	2.2	1000	1800	5/8" OD solid shaft	Stainless Steel
5322C	2.2	1000	1800	5/8" OD solid shaft	Ceramic
5321C-H	2.2	1000	1800	5/8" ID hollow shaft	Stainless Steel
5322C-H	2.2	1000	1800	5/8" ID hollow shaft	Ceramic

Injector Head - Add Suffix "D" - (i.e.: 5321C-DH).

Pressure in PSI and BAR	GPM	HP	GPM	HP	GPM	HP	GPM	HP
	LPM	HP	LPM	HP	LPM	HP	LPM	HP
	@900 RPM		@1200 RPM		@1450 RPM		@1725 RPM	
100 PSI	1.1	0.2	1.5	.3	1.8	.4	2.2	.4
6.9 BAR	4.2	0.2	5.7	.3	6.8	.4	8.3	.4
300 PSI	1.1	.4	1.5	.5	1.8	.6	2.1	.7
20.7 BAR	4.2	.4	5.7	.5	6.8	.6	7.9	.7
500 PSI	1.1	.5	1.5	.6	1.8	.7	2.1	.8
34.5 BAR	4.2	.5	5.7	.6	6.8	.7	7.9	.8
700 PSI	1.1	.6	1.5	.8	1.8	.9	2.1	1.1
48.3 BAR	4.2	.6	5.7	.8	6.8	.9	7.9	1.1
1000 PSI	1.1	.8	1.4	1.0	1.8	1.2	2.1	1.4
69.0 BAR	4.2	.8	5.3	1.0	6.8	1.2	7.9	1.4