

High Pressure, 3 Diaphragm

Model 9910-D813 and D813GRGI

*All HP requirements listed in the table below are electrical.
For approximate gasoline equivalent, multiply by 1.3.*

Pressure in PSI and BAR	GPM	HP	GPM	HP	GPM	HP	GPM	HP
	LPM	HP	LPM	HP	LPM	HP	LPM	HP
	@350 RPM	@450 RPM	@500 RPM	@550 RPM	@550 RPM	@550 RPM	@550 RPM	@550 RPM
0 PSI	14.7	2.2	18.2	2.9	19.7	3.5	21.4	3.6
0 BAR	55.6	2.2	68.7	2.9	74.6	3.5	81	3.6
435 PSI	13.5	4.1	17.3	5.3	19.0	5.9	19.6	6.3
30 BAR	51.1	4.1	65.5	5.3	71.9	5.9	74.2	6.3
580 PSI	13.4	5.3	17.1	6.8	18.3	7.6	19.2	8.1
40 BAR	50.8	5.3	64.8	6.8	69.3	7.6	72.6	8.1
725 PSI	13.3	6.4	16.9	8.4	17.8	9.3	18.7	9.9
50 BAR	50.4	6.4	63.9	8.4	67.5	9.3	70.8	9.9



HYPRO[®]

**Pentair Water
SPRAY GROUP**

375 Fifth Avenue NW • New Brighton, MN 55112-3288
Phone: (651) 766-6300 • 800-424-9776 • Fax: 800-323-6496
www.hypropumps.com