

Ni-Resist or Silver Series XL™

Series 4001 and 4101 12 volt DC 4-Roller Includes Models: 4001N-AEH, 4001XL-AEH, 4101N-AEH, 4101XL-AEH, 4001N-AE2H, 4001XL-AE2H, 4101N-AE2H, 4101XL-AE2H

Series 4101-EH and 4101-E2H	Model 4101N-AEH & 4101XL-AEH				Model 4101N-AE2H & 4101XL-AE2H		
	Volts	PSI	AMPS	GPM	PSI	AMPS	GPM
	12.0 (Battery) Engine Off	0	10.0	6.3		0	—
5		11.3	6.0		10	8.4	5.3
10		12.5	5.8		20	11.8	4.8
15		13.7	5.6		30	13.7	4.65
20		15.1	5.4		40	16.4	4.4
25		16.7	5.2		50	19.6	4.05
30		18.6	5.0		60	22.8	3.65
35		20.3	4.8		70	25.8	3.20
40		22.3	4.6		80	28.9	3.00
45		24.1	4.4		90	31.5	2.75
	50	25.7	4.2	100	34.2	2.60	
13.5 (Alternator) Engine Running	0	10.4	7.5		0	—	—
	5	11.7	7.0		10	9.1	5.9
	10	13.0	6.6		20	11.2	5.6
	15	14.2	6.4		30	13.9	5.25
	20	15.8	6.2		40	16.9	5.0
	25	17.4	6.0		50	19.5	4.7
	30	19.6	5.8		60	22.7	4.35
	35	20.9	5.6		70	25.7	4.0
	40	22.5	5.4		80	29.2	3.6
	45	24.3	5.2		90	31.9	3.4
	50	26.1	5.0	100	34.8	3.2	

Series 4001-EH and 4001-E2H	Model 4001N-AEH & 4001XL-AEH				Model 4001N-AE2H & 4001XL-AE2H		
	Volts	PSI	AMPS	GPM	PSI	AMPS	GPM
	12.0 (Battery) Engine Off	0	12.6	9.0		10	13.9
5		14.1	8.3		20	18.0	7.9
10		15.2	8.1		30	22.2	7.2
15		17.3	7.8		35	25.0	6.9
20		19.7	7.2		40	27.0	6.5
25		22.1	6.7		50	31.6	5.9
30		24.8	6.2		60	36.2	5.4
13.5 (Alternator) Engine Running	0	13.4	10.4		10	14.4	9.9
	5	14.8	9.9		20	18.3	9.1
	10	16.2	9.4		30	22.3	8.5
	15	18.2	8.9		35	24.5	8.3
	20	20.5	8.5		40	27.0	8.0
	25	22.5	8.2		50	31.0	7.3
	30	24.9	7.7	60	36.1	6.8	