

# Ni-Resist or Silver Series XL™

Series 4001 and 4101 12 volt DC 4-Roller Includes Models: 4001N-AEH, 4001XL-AEH, 4101N-AEH, 4101XL-AEH, 4001N-AE2H, 4001XL-AE2H, 4101N-AE2H, 4101XL-AE2H

Model 4101N-AEH & 4101XL-AEH				Model 4101N-AE2H & 4101XL-AE2H		
Volts	BAR	AMPS	LPM	BAR	AMPS	LPM
12.0 (Battery) Engine Off	0	10.0	23.8	0	—	—
	.3	11.3	22.7	.7	8.4	20.0
	.7	12.5	22.0	1.4	11.8	18.2
	1.0	13.7	21.2	2.1	13.7	17.6
	1.4	15.1	20.4	2.8	16.4	16.7
	1.7	16.7	19.7	3.4	19.6	15.3
	2.1	18.6	18.9	4.1	22.8	13.8
	2.4	20.3	18.2	4.8	25.8	12.1
	2.8	22.3	17.4	5.5	28.9	11.4
	3.1	24.1	16.7	6.2	31.5	10.4
3.4	25.7	15.9	6.9	34.2	9.84	
13.5 (Alternator) Engine Running	0	10.4	28.4	0	—	—
	.3	11.7	26.5	.7	9.1	22.3
	.7	13.0	25.0	1.4	11.2	21.2
	1.0	14.2	24.2	2.1	13.9	19.9
	1.4	15.8	23.5	2.8	16.9	18.9
	1.7	17.4	22.7	3.4	19.5	17.8
	2.1	19.6	22.0	4.1	22.7	16.5
	2.4	20.9	21.2	4.8	25.7	15.1
	2.8	22.5	20.4	5.5	29.2	13.6
	3.1	24.3	19.7	6.2	31.9	12.9
3.4	26.1	18.9	6.9	34.8	12.1	

  

Model 4001N-AEH & 4001XL-AEH				Model 4001N-AE2H & 4001XL-AE2H		
Volts	BAR	AMPS	LPM	BAR	AMPS	LPM
12.0 (Battery) Engine Off	0	12.6	34.1	.7	13.9	31.8
	.3	14.1	31.4	1.4	18.0	29.9
	.7	15.2	30.7	2.1	22.2	27.3
	1.0	17.3	29.5	2.4	25.0	26.1
	1.4	19.7	27.3	2.8	27.0	24.6
	1.7	22.1	25.4	3.5	31.6	22.3
	2.1	24.8	23.5	4.1	36.2	20.4
13.5 (Alternator) Engine Running	0	13.4	39.4	.7	14.4	37.5
	.3	14.8	37.5	1.4	18.3	34.4
	.7	16.2	35.6	2.1	22.3	32.2
	1.0	18.2	33.7	2.4	24.5	31.4
	1.4	20.5	32.2	2.8	27.0	30.3
	1.7	22.5	31.0	3.5	31.0	27.6
2.1	24.9	29.1	4.1	36.1	25.7	