

Low Pressure, 4 Diaphragm

Model 9910-D160

*All HP requirements listed in the table below are electrical.
For approximate gasoline equivalent, multiply by 1.3.*

Pressure in PSI and BAR	GPM	HP	GPM	HP	GPM	HP	GPM	HP	GPM	HP
	LPM	HP	LPM	HP	LPM	HP	LPM	HP	LPM	HP
	@ 350 RPM		@ 400 RPM		@ 450 RPM		@ 500 RPM		@ 550 RPM	
0 PSI	27.7	0.7	31.7	0.8	35.7	0.9	38.4	1.3	42.5	1.4
0 BAR	105.0	0.7	120.0	0.8	135.0	0.9	145.4	1.3	160.9	1.4
145 PSI	25.2	2.5	28.8	2.9	32.4	3.3	35.8	3.9	39.4	4.3
10 BAR	95.4	2.5	109.0	2.9	122.6	3.3	135.5	3.9	149.0	4.3
217 PSI	24.7	3.7	28.2	4.2	31.7	4.7	35.2	5.3	38.7	5.8
15 BAR	93.4	3.7	106.7	4.2	120.0	4.7	133.2	5.3	146.5	5.8
290 PSI	24.2	4.5	27.7	5.2	31.2	5.9	34.6	8.7	38.2	7.4
20 BAR	91.7	4.5	104.8	5.2	118.0	5.9	130.9	8.7	5000	7.4



HYPRO[®]

Pentair Water
SPRAY GROUP

375 Fifth Avenue NW • New Brighton, MN 55112-3288
Phone: (651) 766-6300 • 800-424-9776 • Fax: 800-323-6496
www.hypropumps.com