

Low Pressure, 6 Diaphragm

Model 9910-D250

*All HP requirements listed in the table below are electrical.
For approximate gasoline equivalent, multiply by 1.3.*

Pressure in PSI and BAR	GPM	HP	GPM	HP	GPM	HP	GPM	HP	GPM	HP
	LPM	HP	LPM	HP	LPM	HP	LPM	HP	LPM	HP
	@350 RPM		@400 RPM		@450 RPM		@500 RPM		@550 RPM	
0 PSI	41.9	1.3	47.9	1.5	53.9	1.7	59.6	2.5	65.9	2.8
0 BAR	158.6	1.3	181.3	1.5	204.0	1.7	225.4	2.5	249.6	2.8
145 PSI	39.7	3.8	45.3	4.4	51.0	4.9	56.7	5.6	62.4	6.2
10 BAR	150.1	3.8	171.5	4.4	193.0	4.9	214.5	5.6	236.0	6.2
217 PSI	28.9	5.5	44.5	6.3	50.1	7.1	55.5	8.1	61.0	8.9
15 BAR	147.3	5.5	168.4	6.3	189.5	7.1	210.0	8.1	231.0	8.9
290 PSI	38.4	7.2	43.9	8.3	49.4	9.3	55.0	10.4	60.7	11.5
20 BAR	145.2	7.2	16.0	8.3	186.8	9.3	208.2	10.4	229.7	11.5



HYPRO®

Pentair Water
SPRAY GROUP

375 Fifth Avenue NW • New Brighton, MN 55112-3288

Phone: (651) 766-6300 • 800-424-9776 • Fax: 800-323-6496

www.hypropumps.com