

High Pressure, 5 Diaphragm

Model 9910-D1265

*All HP requirements listed in the table below are electrical.
For approximate gasoline equivalent, multiply by 1.3.*

Pressure in PSI and BAR	GPM	HP	GPM	HP	GPM	HP	GPM	HP	GPM	HP
	LPM	HP	LPM	HP	LPM	HP	LPM	HP	LPM	HP
	@350 RPM		@400 RPM		@450 RPM		@500 RPM		@550 RPM	
0 PSI	23.8	3.8	26.8	4.5	29.7	5.1	31.9	5.5	33.3	5.8
0 BAR	90.0	3.8	101.5	4.5	112.6	5.1	120.7	5.5	126.1	5.8
435 PSI	22.4	7.0	25.5	8.0	28.7	9.1	31.4	9.7	32.7	10.2
30 BAR	84.8	7.0	96.7	8.0	108.5	9.1	118.9	9.7	123.9	10.2
580 PSI	22.2	9.1	25.3	10.4	28.4	11.8	31.1	12.5	32.6	12.8
40 BAR	84.2	9.1	95.7	10.4	107.5	11.8	117.7	12.5	123.4	12.8
725 PSI	22.1	11.2	25.0	12.3	28.2	14.6	30.8	15.6	31.4	15.6
50 BAR	83.7	11.2	94.8	12.3	106.8	14.6	116.4	15.6	118.7	15.6



HYPRO[®]

Pentair Water
SPRAY GROUP

375 Fifth Avenue NW • New Brighton, MN 55112-3288
Phone: (651) 766-6300 • 800-424-9776 • Fax: 800-323-6496
www.hypropumps.com