

BACKPACK SPRAYER

Internal Piston with agitator

Ideal for use in greenhouses, agriculture, landscaping, livestock farming, forestry and pest control.

- Ideal for use under the most demanding conditions thanks to the top quality materials and workmanship used to manufacture the sprayer.
- Multipurpose design makes this sprayer perfect for a variety of formula applications.
- Robust, high output pumping system requires less effort from the operator.
- High-quality materials that are corrosion resistant for long life.
- Tank mouth with deep strainer that reduces the risk of spillage when filling.
- Tank lid with carrying handle and wand clips to make transportation and storage easy. One-way ventilation valve in tank lid prevents the operator from getting splashed by formula.
- Mechanical agitation keeps the formula mixed during spraying. It can be removed when not needed.
- Ergonomic pump handle folds upright for transportation and storage.
- Precision adjustable plastic spray nozzle provides spray patterns from fine mist to jet stream.
- Double-braided fiber-reinforced vinyl hose, is chemically resistant and flexible.
- Heavy-duty flow control with large filter for trouble-free spraying.
- Padded shoulder straps allow a fatigue-free spraying.
- Central attachment keeps the sprayer well-balanced.
- Minimal maintenance required. Most service can be performed without tools.
- A wide assortment of accesorioes is available to enhance your spraying performance.



USED MAINLY FOR:



Insecticides



Herbicides




Disinfectants















Medicinal baths
for husbandry



Fertilizers



ACCESSORIES

<p>Brass spray lances (without spray tip, nut or gasket)</p>  <p>E803-085 - 19.7"/50 cm E803-400 - 15.7"/40 cm</p>  <p>E219-195-C with two nozzles, length 19.7" / 50 cm</p>	<p>FVR spray lances (without spray tip, nut or gasket)</p>  <p>E219-136-C - 19.7"/50 cm E219-142-C - 39.4"/1.0 m E219-143-C - 59.1"/1.50 m E219-146-C - 78.7"/2.0 m</p>
<p>Brass extensions (with connector)</p>  <p>E219-500-C -26.4"/67 cm E219-510-C - 39.4"/1.0 m E219-520-C - 47.2"/1.20 m</p>	<p>EXTENSION LANCE:</p> <p>2-nozzle brass extensions</p>  <p>E219-098-C - 15.74" / 40 cm</p>
<p>2-nozzle FVR extensions</p>  <p>E219-140-C - 19.6"/50 cm E219-147-C - 39.37"/20 cm E219-148-C - 28.7"/73 cm</p>	<p>3-nozzle FVR extensions</p>  <p>E219-138-C - 39.4"-de 1 m E219-151-C - 59.1 de 1.5 m</p> <p>3-nozzle brass extensions</p>  <p>219-420-C - 39.4-1.0 m</p>
<p>SCREEN SHIELDS</p> <p>E219-099 -15.7" / 40 cm E219-117 - 8.7" / 22 cm</p> 	<p>COMPLETE NOZZLES</p>  <p>E803-092-C</p>  <p>E219-610-C</p>  <p>E219-710-C</p>

TECHNICAL DATA

SPECIFICATIONS	DESCRIPTION
Tank capacity	4 gal / 15L
Carrying Straps	Cushioned
Pumping system	Internal piston with agitator
Hose	Fiber vinyl-reinforced 3/8 inch (95.25mm)
Shut-off valve	Professional ergonomic with filter
Spray wand	Fiberglass 20.5 inch /52 cm

SPECIFICATIONS	DESCRIPTION
Nozzle	Adjustable plastic
Output per minute at 45 psi (3 bar)	21.3 fl oz (630 ml)
Working pressure	1-6 bar (15-87 psi)
Net weight	11 lbs / 5 kg
Weight with box	11.6 lbs / 5.3 kg
Dimensions	21.2x8.6x15.5" / 54x22x39.5 cm

Due to the interest in technological process we may make technical changes without notice.